


IP 55 650 °C 400 V PP



Puszka 6-wyl.n/t EP-LUX 5x2.5 mm² pusty IP 55

Typ	Kolor	Opak.	Waga	Indeks
		szt.	kg/100 szt.	
EP-LUX IP55	biały RAL 9003	40	6,90	0226-00

NORMA: PN-IEC-60998-1:2006.
Wymiar: 86x86x39 mm




IP 55 650 °C 400 V PP



Puszka 6-wyl.n/t EP-LUX 5x2.5 mm² z wkładem IP 55

Typ	Kolor	Opak.	Waga	Indeks
		szt.	kg/100 szt.	
EP-LUX IP55	biały RAL 9003	40	9,10	0226-01

NORMA: PN-IEC-60998-1:2006.
Wymiar: 86x86x39 mm




IP 55 650 °C 400 V PP



Puszka 6-wyl.n/t MZ EP-LUX 5x2.5 mm² pusty IP 55

Typ	Kolor	Opak.	Waga	Indeks
		szt.	kg/100 szt.	
EP-LUX IP55	biały RAL 9003	40	6,90	0226-10

NORMA: PN-IEC-60998-1:2006.
Z zewnętrznymi uchwytnymi do montażu.
Wymiar: 86x86x39 mm




IP 55 650 °C 400 V PP



Puszka 6-wyl.n/t MZ EP-LUX 5x2.5 mm² z wkładem IP 55

Typ	Kolor	Opak.	Waga	Indeks
		szt.	kg/100 szt.	
EP-LUX IP55	biały RAL 9003	40	9,10	0226-11
	szary RAL 7035	40	9,10	0226-41
	brąz RAL 8028	40	9,10	0226-61

NORMA: PN-IEC-60998-1:2006.
Z zewnętrznymi uchwytnymi do montażu.
Wymiar: 86x86x39 mm




IP 55 650 °C 400 V PP



Puszka odgałęźna 110x110x52 IP 55

Typ	Kolor	Opak.	Waga	Indeks
		szt.	kg/100 szt.	
IP55	biały RAL 9003	18	13,52	0243-10

NORMA: PN-IEC-60998-1:2006.
Wymiary: 109x109x67 mm



IP 55 650 °C 400 V PP



Puszka odgałęźna 110x80x50 IP 55

Typ	Kolor	Opak.	Waga	Indeks
		szt.	kg/100 szt.	
IP 55	biały RAL 9003	20	15,50	0244-00

NORMA: PN-IEC-60998-1:2006.
Wymiar: 118x118x88 mm

