OVE Austrian Electrotechnical Association

Eschenbachgasse 9 | 1010 Wien | Austria ZVR: 327279890 | www.ove.at

OVE Certification

Kahlenberger Str. 2A | 1190 Wien | Austria T +43 1 370 58 06 | certification@ove.at

Validity of ÖVE-Certificates can be checked at www.ove.at



Page 1 of 6

ÖVE-CERTIFICATE

including the entitlement to use the Austrian Safety Mark



Certificate No.: 43-168-13 Valid from: 2021 07 07

until: 2023 07 07

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Company: PC Electric Ges.m.b.H.

Diesseits 145

4973 St. Martin im Innkreis

Austria

Product: Appliance inlets for industrial purposes

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the applicant holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s).: TGM-VA EE 37226

Österreichischer Verband für Elektrotechnik

Head of OVE Certification


Digitally signed by T. Neumayer Email=t neumayer@ove.at

Dipl.-Ing. T. Neumayer

OVE

Wien, 2021 06 17









Certificate No.: 43-168-13 Date: 2021 06 17

Page 2 of 6

Manufacturer:

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Factory location(s):

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Tested and certified according to:

ÖVE/ÖNORM EN 60309-1:2013-03-01 ÖVE/ÖNORM EN 60309-2:2013-03-01 IEC 60309-1:1999 + A1:2005 + A2:2012 IEC 60309-2:1999 + A1:2005 + A2:2012

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

Product: Appliance inlets for industrial purposes

Type designation: Trademark:

Rating:

543 PCE / ELCEE / SIROX / METECEE Rated current: 125 A

Insulation voltage: 690 V 2P+PE

ZI 'I L ID 07 - ID 00/IE

IP 67 or IP 66/IP 67

with pilot contact, wall mounted appliance-inlet

PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet straight





Date: 2021 06 17 Page 3 of 6

743 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet sloping

544 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+PE

IP 67 or IP 66/IP 67

with pilot contact, wall mounted appliance-inlet

PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet straight

744 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet sloping

545 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+N+PE

IP 67 or IP 66/IP 67

with pilot contact, wall mounted appliance-inlet

645 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+N+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet straight

745 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+N+PE

IP 67 or IP 66/IP 67

with pilot contact, appliance-inlet sloping





Date: 2021 06 17 Page 4 of 6

5432 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

without pilot contact, wall mounted appliance-inlet

6432 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

without pilot contact, appliance-inlet straight

7432 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

2P+PE

IP 67 or IP 66/IP 67

without pilot contact, flanged appliance-inlet sloping

5442 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+PE

IP 67 or IP 66/IP 67

without pilot contact, wall mounted appliance-inlet

6442 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+PE

IP 67 or IP 66/IP 67

without pilot contact, appliance-inlet straight

7442 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+PE

IP 67 or IP 66/IP 67

without pilot contact, appliance-inlet sloping

5452 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+N+PE

IP 67 or IP 66/IP 67

without pilot contact, wall mounted appliance-inlet





Date: 2021 06 17 Page 5 of 6

PCE / ELCEE / SIROX / METECEE

Rated current: 125 A
Insulation voltage: 690 V
3P+N+PE
IP 67 or IP 66/IP 67
without pilot contact, appliance-inlet straight

7452 PCE / ELCEE / SIROX / METECEE

Rated current: 125 A Insulation voltage: 690 V

3P+N+PE

IP 67 or IP 66/IP 67

without pilot contact, appliance-inlet sloping





Date: 2021 06 17 Page 6 of 6

Typlist

| Туре | Rated current A | Earthing contact pos. | Rated operating voltage V | Frequency Hz |
|---|-----------------------|-----------------------|--------------------------------------|-----------------|
| 543 5432 643 6432 743 7432 | 125 | 1 | Other ratings | Other ratings |
| | | 2 | >50 | >300 - 500 |
| | | 3 | >50 - 250 | DC |
| | | 4 | 100 – 130 | 50 and 60 |
| | | 6 | 200 – 250 | 50 and 60 |
| | | 7 | 480 – 500 | 50 and 60 |
| | | 8 | >250 | DC |
| | | 9 | 380 – 415 | 50 and 60 |
| | | 10 | >50 | >100 - 300 |
| | | 12 | Supply from an isolating transformer | 50 and 60 |
| 544 5442 644 6442 744 7442 | 125 | 1 | Other ratings | Other ratings |
| | | 2 | >50 | >300 - 500 |
| | | 3 | 380 | 50 |
| | | | 440 | 60 |
| | | 4 | 100 – 130 | 50 and 60 |
| | | 5 | 600 – 690 | 50 and 60 |
| | | 6 | 380 – 415 | 50 and 60 |
| | | 7 | 480 - 500 | 50 and 60 |
| | | 9 | 200 – 250 | 50 and 60 |
| | | 10 | >50 | >100 - 300 |
| | | 11 | 440 – 460 | 60 |
| | | 12 | Supply from an isolating transformer | 50 and 60 |
| 545 5452 645 6452 745 7452 | 125 | 1 | Other ratings | Other ratings |
| | | 2 | >50 | >300 - 500 |
| | | 3 | 220/380 | 50 |
| | | | 250/440 | 60 |
| | | 4 | 57/100 – 75/130 | 50 and 60 |
| | | 5 | 347/600 – 400/690 | 50 and 60 |
| | | 6 | 200/346 – 240/415 | 50 and 60 |
| | | 7 | 277/480 – 288/500 | 50 and 60 |
| | | 9 | 120/208 — 144/250 | 50 and 60 |
| | | 10 | >50 | >100 - 300 |
| | | 11 | 250/440 – 265/460 | 60 |
| | | 12 | Supply from an isolating transformer | 50 and 60 |

Additional component:



OVE Certification

